

Laser fume



Dust and smoke



Soldering fume



Odors, gases, vapors



Oil and emulsion mists



Additive manufacturing



Complete solutions



Battery cell production . •



Process air drying

Extraction and filtration technology – product overview



Extraction and filtration technologies for airborne pollutants

ULT develops and produces extraction and filtration solutions for all industrial processes that release airborne pollutants - protecting humans, machinery, and products. This also applies to the most modern manufacturing processes. Depending on the application, storage or cartridge filter devices are the technology of choice, sometimes combinations thereof. ULT offers a well-graded range of high quality extraction and filtration systems. In many cases, however, an adaptation to the customer's local conditions is required. The product overview provides a pre-selection in the first stage. Thereafter, we look forward to hearing from you.



JUMBO Filtertrolley 2.0



LAS 160.1

Storage filter system

Storage filter systems are equipped with replaceable filter modules. They are primarily designed for low to medium pollutant concentrations and sticky dusts. In some devices, various filter modules are combined to achieve a maximum separation rate. If the composition of the respective air pollutants requires it, appropriate filter combinations are used to ensure the greatest possible separation rate. Storage filter devices are mostly mobile and space-saving.



ACD 200.1









Laser processing of metals, plastics, glass, organic materials, laser medicine, etc. DUST AND SMOKE

Filling, dosing, sinter-

ing, grinding, cutting,

milling, etc.





All manual and automated soldering operations, etc. Bonding, casting, laminating, cleaning, coating, dosing, etc.

| LAS series | ASD series | LRA series | ACD series | - |
|-------------------------|-------------------------|-------------------------|-------------------------|-------------|
| JUMBO Filtertrolley LAS | JUMBO Filtertrolley ASD | JUMBO Filtertrolley LRA | JUMBO Filtertrolley ACD | 80 m³/h |
| LAS 160.1 | ASD 160.1 | LRA 160.1 | ACD 160.1 | |
| LAS 200.1 | ASD 200.1 | LRA 200.1 | ACD 200.1 | flow |
| LAS 260.1 | | | ACD 220 Ex | e flo |
| LAS 300 | ASD 300 | | | Ĕ |
| LAS 400.1 | ASD 400.1 | LRA 400.1 | ACD 400.1 | volume |
| LAS 500 | ASD 500 | | | ses |
| LAS 800 | | | | classes |
| LAS 1200 | ASD 1200 | LRA 1200 | ACD 1200 | |
| LAS 1500 | ASD 1500 | | | anc |
| LAS 2000 | ASD 2000 | | | Performance |
| LAS 2500 | ASD 2500 | | | erfo |
| LAS 3000 | | | | <u> </u> |
| | Airline 4P | | | ¯↓ |
| | Airline 6P | | | 10,000 m |

Storage filter systems

Cartridge filter systems

Available as both storage and cartridge filter systems

Additional solutions



Cartridge filter systems

Cartridge filter systems are equipped with integral, cleanable filter elements. They are utilized for medium to large pollutant concentrations, preferrably for dry particles. Cartridge filter units are mainly used stationary. If pollutant composition and amount require a special solution, ULT designs combinational systems of cartridge and storage filter modules - in close cooperation with our customers.





Benefits

HIGHLY EFFECTIVE

Fume extraction technology from ULT achieves maximum efficiency through high-quality drives, perfect management of flow mechanics, and innovative filtration concepts.

LOW MAINTENANCE

ULT's extraction and filtration technology permits long maintenance intervals, making it perfectly suitable for automated production. Easy and low-contamination filter exchange.

OPEN TO SPECIAL REQUIREMENTS

Many devices are available in alternative versions with a variety of accessories: ESD or explosion protection, stainless steel enclosures, with integrated control, or interfaces for external control.

USER-FRIENDLY

The units are easy to operate, require low energy efforts, and feature extraordinary low noise levels.

FLEXIBLE

Our systems can be combined with extraction arms or cabinets, suction hoses and tables, or even be integrated into production cells. They can be individually adapted to a multitude of applications ULT is certified in compliance with Std. ISO 9001:2015. The plants are designed according to international standards. If required, they will be certified according to ATEX and W3 and tested to meet H requirements.

In addition, the plants always comply with current EC directives on energy efficiency (ErP directive: Total energy efficiency of ready-to-use ventilation systems or minimum energy efficiency of electric motors).

Detailed technical information can be found on device specific data sheets or on our website. All technical data is general and not binding and does not guarantee the suitability of a product for a specific application.

Made in Germany.

ULT AG

Am Göpelteich 1 02708 Löbau, Germany

 Phone:
 +49 3585 4128 0

 Fax:
 +49 3585 4128 11

 Email:
 ult@ult.de

 Web:
 www.ult-airtec.com

